

## VÁLVULA HORIZONTAL 60 | BONDE 60 HORIZONTALE HORIZONTAL DRAINS 60 | VALVOLA ORIZZONTALE 60

ES | TORNILLOS INOXIDABLES  
FR | VIS ACIER INOXYDABLE  
EN | STAINLESS STEEL SCREWS  
IT | VITI IN ACCIAIO INOSSIDABILE



ES | SÓLO QUITAR ESTE TAPÓN EN CASO DE TENER BOTE SIFÓNICO EN LA INSTALACIÓN  
FR | RETIREZ CE BOUCHON UNIQUEMENT SI VOUS AVEZ UNE BOÎTE SIPHONIQUE DANS L'INSTALLATION  
EN | REMOVE ONLY IN CASE OF HAVING OTHER TRAP IN THE IN THE INSTALLATION  
IT | RIMUOVERE QUESTO TAPPO SOLO SE PRESENTE ALTRO SIFONE NELL'IMPIANTO



ES | BRIDA DE ACERO INOXIDABLE  
FR | BRIDE EN ACIER INOXYDABLE  
EN | STAINLESS STEEL FLANGE  
IT | FLANGIA IN ACCIAIO INOSSIDABILE



ES | JUNTA DE CAUCHO  
FR | CONSEIL EN CAOUTCHOUC  
EN | RUBBER BOARD  
IT | SCHEDA DI GOMMA



ES | TUERCA Y JUNTA  
FR | ECROU ET JOINT  
EN | NUT AND GASKET  
IT | DADO E GUARNIZIONE



ES | CUERPO VÁLVULA  
FR | CORPS DE BONDE  
EN | DRAINS BODY  
IT | CORPO VALVOLA



### CAUDAL | DÉBIT | FLOW | FLUSSO

ES | CON 15 MM DE AGUA: 35L/MIN  
FR | AVEC 15 MM. D'EAU: 35L/MIN  
EN | WITH 15 MM. WATER: 35L/MIN  
IT | CON 15 MM. DI ACQUA: 35L/MIN

TEMP. MAX. 100°C

EN 1253-1:2014  
EN 1253-2:2014