

VÁLVULA TRIPLE SIFÓN | BONDE À TRIPLE SIPHON TRIPLE SIPHON DRAIN | VALVOLA A TRIPLO SIFONE | DREIFACH-SIPHONVENTIL

ES | **VASO SIFÓNICO**
FR | SIPHON
EN | SIPHONIC CUP
IT | SIFONE
DK | SIPHONBECHER



ES | **TORNILLOS INOXIDABLES**
FR | VIS ACIER INOXYDABLE
EN | STAINLESS STEEL SCREWS
IT | VITI IN ACCIAIO INOSSIDABILE
DK | ROSTFREIE SCHRAUBEN

ES | **BRIDA DE PVC**
FR | BRIDE EN PVC
EN | PVC FLANGE
IT | FLANGIA IN PVC
DK | FLANSCH AUS PVC



ES | **JUNTA DE CAUCHO**
FR | CONSEIL EN CAOUTCHOUC
EN | RUBBER BOARD
IT | SCHEDA DI GOMMA
DK | GUMMI-DICHTUNG



ES | **CUERPO VÁLVULA**
FR | CORPS DE BONDE
EN | DRAINS BODY
IT | CORPO VALVOLA
DK | VENTILGEHÄUSE



ES | **TUERCA Y JUNTA**
FR | ECROU ET JOINT
EN | NUT AND GASKET
IT | DADO E GUARNIZIONE
DK | MUTTER UND DICHTUNG



ES | **GANCHO PARA EXTRAER VASO SIFÓNICO**
FR | CROCHET POUR EXTRAIRE LE CODET SIPHONIQUE
EN | TRAP CUP REMOVAL HOOK
IT | GANCIO PER ESTRARRE IL BICCHIERE SIFONICO
DK | HAKEN ZUM HERAUSZIEHEN DES SIPHONBECHERS



CAUDAL | DÉBIT | FLOW | FLUSSO | DURCHFLOSSMENGE

ES | **CON 15 MM DE AGUA: 40L/MIN**
FR | AVEC 15 MM. D'EAU: 40L/MIN
EN | WITH 15 MM. WATER: 40L/MIN
IT | CON 15 MM. DI ACQUA: 40L/MIN
DK | BEI 15 MM WASSER: 40L/MIN

TEMP. MAX. 100°C

CE
EN 1253-1:2014
EN 1253-2:2014

